

Suncover



An implement for setting up and removing large width row covers

Suntex CP

N Americas only supplier of German Engineered Covertan Pro offers you huge savings in Labor to apply, remove and re-use Row Covers.

Suncover Features

Fast:

- 3 workers maximum
- Application and removal speed: 5-6 km/hour or 10 Ha (22 acres) per day

Economical

- Reduce your Row Cover Labor application, removal and replacement costs.

Exclusive: Suntex CP unfolded rolls on PVC cores for Suncover

- Sizes: Rolls up to 7.9 m (26') x 500 m (1640')
With reinforced edges.



Suncover



Digging the furrow



Burying the row cover

Fast, economic, strong

Characteristics

Setting up :

- on the 3 points hitch
- the row cover is grabbed and guided by a wheel
- a disk covers the row cover with soil

Removing :

- on the tractor's front hitch
- a bowed bar is placed on the frame of the machine so it stretches the row cover and the soil is loosened and dropped
- perfect rolling up of the row cover thanks to :
 - an hydraulic engine with regulated output
 - the frame that articulates left and right
- removal of row covers on a single roll (2000 m maximum)

Transportation :

- done in less than 10 minutes
- minimal clutter

USE REQUIREMENTS :

- At least a 80 H P, 4 wheel drive
- Back hitch for setting up
- Front hitch of 2500 kg of capacity for the removal

Suncover

- Length: 9 m (30')
- Width: 2.6 m (8.5')
- Height: 2.30 m (7.5')
- Weight: 1550 Kg (3450 lbs.) – without roll



Transportation



Tel: 1.941.706.0008 w: suntexcp.com

Tel: 1.416.738.8888 e: chris@suntexcp.com

Sarasota, FL

Sayreville, NJ

Toronto, ON